





24" High Thrift Air "T296" Slant Canopy With Rear Tempered Make Up

ICC/IMC		Filt W
LI E		

Job Name:						
Dealer:						
P.O. #:	By:	Date:				
Fabrication cannot	begin until	sheet is signed				
Approved by		Date				

Air Wall Paneling

T2 RM	DIMENSIONAL DATA								
"W"	"B"	"H"	"T"	"F"	"D"	"M"	"P"	"0"	
36"	231/2"	25"	12"	20"	9"				
42"	231/2"	25"	18"	20"	14"				
48"	231/2"	25"	24"	20"	21"				
54"	231/2"	25"	30"	25"	21"				
60"	231⁄2"	25"	22"	25"	20"				

Specifications

T296S0 Series Thrift Air Exhaust Canopy: Sturdi-Bilt Canopy constructed of 20 Gauge Stainless Steel #3 polish on all exposed surfaces. Balance 18 Gauge Aluminized Steel. All Externally Welded Seams, Code #96 Construction. Includes a full compliment of 20" wide U.L. Listed Heavy Duty Galvanized Steel Baffle Filters, Pitched Rear Grease Gutter, Grease Drain and removable Grease Cup. Front and Rear Hanger Brackets for threaded rod. NSF Listed, Built to NFPA #96, and International Mechanical Code Type I Hood Standards.

Rear Make Up Air Plenum: Distributes Tempered air behind the canopy in an rear S/S make up air plenum.

T296A8 Series Thrift Air Exhaust Canopy: Same only all 18 Gauge Aluminized Steel Painted Gray where exposed.

Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incan-

descent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy Light Fixture, Mounting Plate, External Junction Box, not prewired.

UL 710 and Canada CSA C22.2 No 113. Canopy Labeled and Listed UL 710

•

•

•

•

•

•

•



Can/CSA C22.2

8132 Puritan Avenue, Detroit, Michigan, 48238 - Phone Toll Free - 1-800-521-2895 - Fax Toll Free 1-800-444-2895