



APPROVAL SHEET



Thrift Air "TB96" Box Style Canopy

	Exhaus			1 & E		_	ains
	Job Name:						
	Dealer:						
	Canopy Model			Ву:		Date:	
	Fabrication cannot		begin until sheet is signed			igned	
	Approved by			lumber	Date		
	Exit	Duc	et S	Size	e: _	"X	
H	TBEC PLN	DIMENSIONAL DATA					
B	"W"	"B"	"H"	"T"	"F"	"D"	"E"
* W —	36"	161/2"	18"	19"	16"		
© E	42"	161/2"	18"	25"	16"		
	48"	161/2"	18"	19"	16"		
	54"	161/2"	18"	25"	16"		
		4.01/11	1011	2011	16"		
	60"	161/2"	18"	30"	10"		

Specifications
TB96S0 Series Thrift Air Box Style Exhaust Canopy: Sturdi-Bilt Canopy constructed of 20 Gauge Stainless Steel
#3 polish on all exposed surfaces. Balance 18 Gauge Aluminized Steel. All Externally Welded Seams, Code #96 Construc-
tion. Includes a full compliment of 20" wide U.L. Listed Aluminum Baffle Filters, Pitched Rear Grease Gutter, Grease Drain
and removable Grease Cup. Front and Rear Hanger Brackets for threaded rod. NSF Listed, Built to NFPA #96, and Interna-
tional Mechanical Code Type I Hood Standards.
Exhaust Plenum : Externally welded NFPA#96 16 Gauge Aluminized Steel Plenm with two welded canopy connections
which allows one exhaust duct to serve hood.
End Curtains: Light Gauge S/S End Curtains to improve efficiency and lower required CFM
TB96A8 Series Thrift Air Box Style Exhaust Canopy: Sturdi-Bilt Canopy same as above only constructed of 18
Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.
Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incan-
descent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy Light
Fixture, Mounting Plate, External Junction Box, not prewired.
UL 710, Canada CSA C22.2 No 113 UL 710 Canony Labeled and Listed Canony Labeled and Listed Canony Labeled and Listed Canony Labeled and Listed Canony Labeled and Listed