



## APPROVAL SHEET



## Thrift Air T2M96 24" Hi Make Up Air Canopy

With Rear Insulated Untempered Make Up Air Plenum

								With En	With End Curtains				
$\bigcap$	$\leq$							Job Name:	Job Name:				
										Dealer:	Dealer:		
										P.O. #:	Ву:	Date:	
										Fabrication cannot	begin until	sheet is signed	
										Approved by	Approved by Date		
T2M RMUA													
W	В	Н	T	D	F	M	MP	Р	0	В	Filt		
36"	24"	25½"								1	V	v	
42"	24"	25½"											
48"	24"	25½"	18"	16"	20"	12"				P			
54"	24"	25½"	18"	16"	20"	12"							
Shorilinations													
	<b>Specifications</b> T2M96SO Series 24" High Thrift Air Make Up Air Canopy: Sturdi-Bilt Compensating Canopy for air												
• •#3 p	conditioned kitchens and kitchens with low ceilings constructed of 20 Gauge Stainless Steel colish on all exposed surfaces. Balance 18 Gauge Aluminized Steel. All Externally Welded Seams,												
• Code #96 Construction. Insulated Make Up Air Plenum with full length diffusers. Includes a full													
compliment of 20" wide U.L. Listed Aluminum Baffle Filters, Pitched Rear Grease Gutter, Grease Drain and removable Grease Cup. Front and Rear Hanger Brackets. NSF Listed, Built to NFPA #96 and													
• International Mechanical Code Type I Hood Standards.													
End Curtains: Light Gauge S/S End Curtains to improve efficiency and lower required CFM													
• <b>Rear Make Up Air Plenum:</b> Distributes Untempered Make Up Air behind the Canopy in an Insulated S/S Where  • Shows Rear Make Up Air Plenum.													
T2M96A8 Series 24" High Thrift Air Make Up Air Exhaust Canopy: Sturdi-Bilt Canopy same as													
<ul> <li>above only constructed of 18 Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.</li> <li>Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Wa</li> </ul>													
Incandescent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass													
Globe, Canopy Light Fixture, Mounting Plate, Junction Box, prewired to External Junction Box.													
	S/S Wall Paneling: 20 Gauge S/S Wall Paneling with Aluminum Trim. 36" Hi UL 710 UL 710												
Cano		halad a	ndIi	ictod	ભ	23LV						•	