



APPROVAL SHEET



CANOPIES, UPDRAFTS, DUCTWORK, EXHAUST AND MAKE UP AIR FANS

Thrift Air T2M96 24" Hi Make Up Air Canopy

With Exhaust Plenum, End Curtains, & Rear Tempered Make Up Air Panels

	M
	E / M / M / W / W
ICCIMC	P

Job Name:		
Dealer:		
Canopy Model	Ву:	Date:
Fabrication cannot	begin until	sheet is signed
Approved by	PO Number	Date

Exit Duct Size: __"x __"

T2MPL RMUA	DIMENSIONAL DATA							
W	В	T	D	Fil	M	MP	Р	E
36"	24"							
42"	24"							
48"	24"	18"	16"	20"	12"	·		
54"	24"	18"	16"	20"	12"			

Specifications				
T2M96S0 Series 24" High Thrift Air Make Up Air Canopy: Sturdi-Bilt Compensating Canopy for air				
• conditioned kitchens and kitchens with low ceilings constructed of 20 Gauge Stainless Steel #3 polish on all				
exposed surfaces. Balance 18 Gauge Aluminized Steel. All Externally Welded Seams, Code #96 Construction. Insulated				
• Make Up Air Plenum with full length diffusers. Includes a full compliment of 20" wide U.L. Listed Aluminum Baffle Filters,				
Pitched Rear Grease Gutter, Grease Drain and removable Grease Cup. Front and Rear Hanger Brackets. NSF Listed, Built				
to NFPA #96 and International Mechanical Code Type I Hood Standards.				
• Exhaust Plenum: Externally welded NFPA#96 16 Gauge Aluminized Steel Plenm with two welded canopy connections				
which allows one exhaust duct to serve hood.				
• End Curtains: Light Gauge S/S End Curtains to improve efficiency and lower required CFM				
T2M96A8 Series 24" High Thrift Air Make Up Air Exhaust Canopy: Sturdi-Bilt Canopy same as above only constructed of 18 Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray				
• Constructed of 18 Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.				
Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incan-				
descent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy				
Light Fixture, Mounting Plate, Junction Box, prewired to External Junction Box.				
S/S Wall Paneling: 20 Gauge S/S Wall Paneling with Aluminum Trim. 36" Hi				
UL 710 (I) ZILV				
Canony Labeled and Listed				