



APPROVAL



Thrift Air **T2M96** 24" Hi Make Up Air Canopy

	With E	xhaust	Ple	nu	m 8	& Er	nd	Curta	ains	
		Job Name:								
		Dealer:								
		Canopy Model			Ву:		D	Date:		
		Fabrication cannot			begin until		sh	sheet is signed		
		Approved by			PO Number		Da	Date		
TB D	TF M	Exit Duct Size:"x								
H		T2M PLN DIMENSIONAL DATA								
BF		W	В	T	D	F	M	OA	D	
Wi	dth /	36"	24"							
		42"	24"							
		48"	24"	18"	16"	20"	12"			
		54"	24"	18"	16"	20"	12"			
Specifications										
T2M96S0 Series 24" High Thriff conditioned kitchens and kitchens wi exposed surfaces. Balance 18 Gauge Alumin Make Up Air Plenum with full length diffuse Pitched Rear Grease Gutter, Grease Drain ar to NFPA #96 and International Mechanical Exhaust Plenum: Externally welded NFP which allows one exhaust duct to serve hoo	It Air Make Up Air Cand th low ceilings constructed it low ceilings constructed it low ceilings constructed it low ceilings a full complimed removable Grease Cup. Code Type I Hood Stand PA#96 16 Gauge Aluminiz	opy: Sturdi-Ed of 20 Gaug Welded Seament of 20" w Front and Reards.	ge Sta ms, C ide U. ear Ha	inles: ode # L. Li inger	s Stee 196 Co Isted A Brack	el #3 p onstru Alumin kets. N	olish ction num ISF I	on all Insulate Baffle Fi Listed, Bu	lters, ıilt	

T2M96A8 Series 24" High Thrift Air Make Up Air Exhaust Canopy: Sturdi-Bilt Canopy same as above only

End Curtains: Light Gauge S/S End Curtains to improve efficiency and lower required CFM

S/S Wall Paneling: 20 Gauge S/S Wall Paneling with Aluminum Trim. ______" Hi

• Light Fixture, Mounting Plate, Junction Box, prewired to External Junction Box.

(UL) LISTED

UL 710

Canopy Labeled and Listed EXHAUST HOOD WITHOUT

constructed of 18 Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.

Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incandescent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy