




APPROVAL SHEET




Thrift Air "TL96" Low Ceiling Canopy

With 3" NFPA Air Space With Exhaust Plenum



Job Name:		
Dealer:		
Canopy Model	Ву:	Date:
Fabrication cannot	begin until	sheet is signed
Approved by	PO Number	Date



Light Fixture, Mounting Plate, External Junction Box, not prewired.

Exit Duct Size:"x								
LAS PLN	DIMENSIONAL DATA							
"W"	"CW"	"B"	"T"	"F"	"FH"	"D"	"OA"	
39"	36"	16"	15"	16"	9"			
45"	42"	16"	15"	16"	9"			
51"	48"	16"	20"	16"	9"			
57"	54"	16"	20"	16"	9"			

•	Specifications
•	TL96S0 Series Thrift Air Low Ceiling Exhaust Canopy: Sturdi-Bilt Canopy constructed of 20 Gauge Stainless
•	Steel #3 polish on all exposed surfaces. Balance 18 Gauge Aluminized Steel. Designed for Kitchens with low ceilings,
	only 7ft3" to top of canopy after hanging at 6ft6". All Externally Welded Seams, Code #96 Construction. Includes a full
	compliment of 20" wide U.L. Listed Aluminum Baffle Filters, Pitched Rear Grease Gutter, Grease Drain and removable
	Grease Cup. Front and Rear Hanger Brackets for threaded rod. NSF Listed, Built to NFPA #96 and, International Me-
	chanical Code Type I Hood Standards.
	Exhaust Plenum : Externally welded NFPA#96 16 Gauge Aluminized Steel Plenm with two welded canopy connections
	which allows one exhaust duct to serve hood.
	Air Space: 3" NFPA Air Space at Rear of Canopy for 3" clearance to limited combustible material, same material as hood.
	TL9A8 Series Thrift Air Low Ceiling Exhaust Canopy: Sturdi-Bilt Canopy same as above only constructed of 18
•	Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.
•	S/S Wall Paneling: 20 Gauge S/S Wall Paneling with Aluminum Trim" Hi
•	Vapor Proof Canopy Light: Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incan
-	descent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy

63"