



CANOPIES, UPDRAFTS, DUCTWORK, EXHAUST AND MAKE UP AIR FANS




APPROVAL  
SHEET




Standard 2

# Thrift Air "TLB96" Low Ceiling Box Canopy

## With 3" NFPA Air Space



Job Name:		
Dealer:		
Canopy Model	By:	Date:
<b>Fabrication cannot begin until sheet is signed</b>		
Approved by	PO Number	Date



TLB AS		DIMENSIONAL DATA					
"W"	"CW"	"B"	"H"	"T"	"Filt"	"FH"	"D"
39"	36"	16"	17½"	15"	16"	12"	10"
45"	42"	16"	17½"	15"	16"	12"	10"
51"	48"	16"	17½"	20"	16"	12"	12"
57"	54"	16"	17½"	27"	16"	12"	13"
63"	60"	16"	17½"	20"	16"	12"	12"

### Specifications

- ☐ **TLB96S0 Series Thrift Air Low Box Ceiling Exhaust Canopy:** Sturdi-Bilt Canopy constructed of 20 Gauge Stainless Steel #3 polish on all exposed surfaces. Balance 18 Gauge Aluminized Steel. Designed for Kitchens with low ceilings, only 7ft3" to top of canopy after hanging at 6ft6". All Externally Welded Seams, Code #96 Construction. Includes a full compliment of 20" wide U.L. Listed Aluminum Baffle Filters, Pitched Rear Grease Gutter, Grease Drain and removable Grease Cup. Front and Rear Hanger Brackets for threaded rod. NSF Listed, Built to NFPA #96 and, International Mechanical Code Type I Hood Standards.
- ☐ **Air Space:** NFPA 3" Air Space on (back) (left) (right) for use on fire rated drywall on steel stud walls
- ☐ **TLB9A8 Series Thrift Air Low Ceiling Box Exhaust Canopy:** Sturdi-Bilt Canopy same as above only constructed of 18 Gauge Aluminized Steel. All Exposed surfaces painted hammertone Gray.
- ☐ **S/S Wall Paneling:** 20 Gauge S/S Wall Paneling with Aluminum Trim. \_\_\_\_\_" Hi
- ☐ **Vapor Proof Canopy Light:** Sturdi-Bilt Fireguard Canopy Light, U.L. and NSF Listed 100 Watt Incandescent Vapor and Grease proof Canopy Light. Included Plastic Coated Lime Glass Globe, Canopy Light Fixture, Mounting Plate, External Junction Box, not prewired.

