



## **APPROVAL SHEET**



CANOPIES, UPDRAFTS, DUCTWORK, EXHAUST AND MAKE UP AIR FANS

## **Oven Canopys**

Type II Baking consists of the baking, and rethermalizing of precooked items. The use of any uncooked meat requires the use of a Type Note: Type II 1 Hood. **Baking Only** 

"D1"	' Ser	ies	"C	ap" S	Style
	Rear	Mak	<b>(e</b>	Up	Air
Joh Name					

Job Name:		
Dealer:		
P.O. #:	Date:	
Oven Make	Oven Model	
Canopy Model	Date:	By:

## **D1 Series**

Overhang	Overhang
Oven Size	<b>─</b> ∤12"∤
Removable Filters	
Flat Top Ove	n
1	$\overline{}$

	xhaus uctwo		¥ 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	Make Up Air Ductwork √√√√√√
		Flue Char	nber	EE S S
			Ove	

## Specifications

	"D1S" SeriesConveyor Oven Canopy: Constructed of minimum 20 Gauge Stainless Steel
	Where Shows, 20 Gauge Minimum Aluminized Steel Back, Bottom and Top, Welded Construciton. 12"
	Overhang for flat top single deck ovens. Air Filter Panel. Ceiling hung, designed to mount directly over
	the oven. International Mechanical Type II Hood, NSF Listed. All Canopys custom built to fit specified
	Conveyor Oven, Oven Make and Model must be specified.
$\neg$	(/D4   11   G   1   G

"D1A" SeriesConveyor Oven Canopy: Same as above, only constructed of all minimum 20
Gauge Aluminzed Steel, Painted Hammertone Gray exposed Front and Ends.

<b>Type 1 NFPA #96 Construction:</b>	Constructed of 18	Gauge all externally	welded construction	ı, UL
Grease Listed Baffle Filters, pitched g	gutter, grease cup.			

**Flue:** Canopy has built in flue chamber to vent oven flue.